

STEEL CYLINDER SPECIFICATIONS:

X-Series

High Pressure - 230 bar service pressure

Five different models, Two different diameters

Description	X-Series 80	X-Series 100	X-Series 120	X-Series 119	X-Series 130
Model	X7-80	X7-100	X7-120	X8-119	X8-130
Service Pressure	230 bar	230 bar	230 bar	230 bar	230 bar
Nominal Capacity	10.1 liters	12.2 liters	15.3 liters	14.8 liters	16.0 liters
Buoyancy* FULL	- 4.1 kg	- 4.5 kg	- 4.9 kg	- 4.9 kg	- 5.3 kg
Buoyancy* EMPTY	- 1.4 kg	- 1.1 kg	- 0.9 kg	- 0.9 kg	- 0.9 kg
Weight EMPTY	13.1 kg	15.0 kg	17.2 kg	19.0 kg	19.5 kg
Outside Diameter	184 mm	184 mm	184 mm	203 mm	203 mm
Cylinder Length	50.0 cm	60.1 cm	71.1 cm	60.1 cm	64.8 cm
Valve Included	VA200	VA200	VA200	VA200	VA200

*in sea water with valve

LP-Series

Low Pressure - 230 bar service pressure

Four different models, Two different diameters

Description	LP Series 85	LP Series 95	LP Series 108	LP Series 121
Model	LP85	LP95	LP108	LP121
Service Pressure	184 bar	184 bar	184 bar	184 bar
Nominal Capacity	12.8 liters	14.8 liters	16.8 liters	18.9 liters
Buoyancy* FULL	- 2.7 kg	- 3.6 kg	- 3.6 kg	- 4.1 kg
Buoyancy* EMPTY	- 1.0 kg	- 1.5 kg	- 0.5 kg	- 0.5 kg
Weight EMPTY	15.6 kg	18.5 kg	20.2 kg	22.0 kg
Outside Diameter	184 mm	203 mm	203 mm	203 mm
Cylinder Length	65.3 cm	60.1 cm	67.9 cm	75.0 cm
Valve Included	VA200	VA200	VA200	VA200

*in sea water with valve

Pony Series

3AA Steel @ 230 bar service pressure

Four different models, Two different diameters

Description	X4 Pony 13	X4 Pony 19	X5 Pony 30	X5 Pony 40
Model	X4-13	X4-19	X5-30	X5-40
Service Pressure	230 bar	230 bar	230 bar	230 bar
Nominal Capacity	1.8 liters	2.6 liters	4.0 liters	5.3 liters
Buoyancy* FULL	- 1.5 kg	- 1.7 kg	- 2.7 kg	- 2.9 kg
Buoyancy* EMPTY	- 1.5 kg	- 1.5 kg	- 2.2 kg	- 1.9 kg
Weight EMPTY	3.1 kg	4.2 kg	6.8 kg	8.2 kg
Outside Diameter	108 mm	108 mm	137 mm	137 mm
Cylinder Length	31.1 cm	41.3 cm	37.5 cm	47.6 cm
Valve Included	VA200	VA200	VA200	VA200

*in sea water with valve