


# LT360 USB RECHARGEABLE DIVE LIGHT

### **Battery Installation**



# **Battery Installation**

Insert 1 ea. 26650 Li-ion battery with the positive "+" end facing the flashlight head. Exercise caution to get the battery polarity correct.

#### **Button Switch**


- The button switch is a 3-position switch, High-Mid-Off.
- The button switch indicates the battery's voltage: green for high and red for low.

#### Charging

- Unscrew and remove the rear cap of the light to expose the charging port. The light head can remain in place.
- Be sure to dry the port if there is any moisture present from the previous dive. This will prevent oxidation
- Plug the USB cable into the provided wall charger or any convenient USB charging port
- Plug the Micro USB connector into the charging port on the back of the light
- When the charge indicator is red, it means that it is charging.
   When the charge indicator turns green, it means that charging is complete.
- · Remove from charger when fully charged
- · Do not use light while it is charging
- Inspect the o-rings to make sure that they are clean and free
  of any lint, hair or debris. Place a light film of silicone grease
  on the o-rings. This will make removal / replacement of rear
  cap much easier.
- Carefully thread the rear cap back on to the body being careful not to pinch or unseat o-rings.

#### Care and Maintenance

- After each dive, rinse your light thoroughly with clean, fresh water
- · If you are going to open the light, dry with towel first.
- Keep all o-rings cleaned and lubricated with a light coating of silicone grease. There are o-rings under the head and under the tail cap
- Store light in a cool place, out of direct sunlight and away from heat sources.



#### **Features**

Power Source CREE XPG2-S3 (x3) LED

Output High 1000 lm Mid 500 lm

Burn Time High - 2.3hr. Low - 4.5hr.

Battery 5000mAh 4.2V Li-ion Battery

Charge Time Charges in 3 hours

Switch 3-position (High-Mid-Off) button

switch

Beam Distance 623 ft. (190 m)
Beam Angle 20 degrees

Impact Resistant 1 m

Depth Tested 328 ft. (100 m)
Length 6.1 in. (156 mm)
Head Diameter 1.7 in. (44 mm)
Body Diameter 1.3 in. (32 mm)
Weight (including battery) 9.9 oz. (281g)

### Notice:

The stated data has been measured according to the international flashlight testing standards in the laboratory. The data may vary with environmental conditions.

## Warranty:

- · Your XS Scuba light is covered by a full 12 month warranty.
- Within 14 days of purchase, if a fault occurs due to defect, the light will be replaced (proof of purchase required).
- After 14 days and within 12 months of purchase, your light will be repaired or replaced at the discretion of XS Scuba.
- Excluded is damage caused by incorrect battery insertion (reversed polarity), battery leakage, disassembly, modification or abuse.