

4040 W. Chandler Ave Santa Ana, CA 92704

> p. 866.977.2822 f. 800.248.5430

www.XSscuba.com

XS Scuba Low-Pressure Regulator Hoses

Specification Sheet





- 3/8"-24 UNF Male to 9/16"-18 UNF Female
- Designated by XS logo on the male fitting
- Date code etched into male fitting
- Meets all EN250 norms
- Exceeds pull test requirement of 1000N (102kg)
- Internal diameter: 6.5 mm External diameter: 12 mm
- Hose material: Thermo plastic rubber
- Hose fittings: Stainless Steel • Working pressure: 350 psi • Burst pressure: 2000 psi
- Hose printing: WARNING-DO NOT EXCEED 350PSI-HIGHER PSI MAY CAUSE DAMAGE OR PERSONAL INJURY
- Color: Black, unless denoted otherwise

| Inches | CM | Part# |
|--------|------|-------------------|
| 22 | 56 | LP22 |
| 24 | 61 | LP24 |
| 26 | 66 | LP26 |
| 28 | 71 | LP28 |
| 30 | 76 | LP30 |
| 32 | 81 | LP32 |
| 36 | 91 | LP36 |
| 36 | 91 | LP36YL (Yellow) |
| 40 | 102 | LP40 |
| 40 | 102 | LP40GN (Green) |
| 60 | 152 | LP60 |
| 84 | 213 | LP84 |
| 300 | 762 | LP300YL (Yellow) |
| 600 | 1524 | LP600YL (Yellow) |
| 1200 | 3048 | LP1200YL (Yellow) |
| 1800 | 4572 | LP1800YL (Yellow) |





